



Tube Dia øD mm	Rod Dia ød mm	A	E	P	R	L	M	N	RB	C	
50	32	250	85	65	35	24	26	45	32.5	25	with lock nut (adjustable)
63	40	255	86	75	35	24	26	45	37.5	32	
80	50	325	101	95	50	30	32	52	47.5	40	
100	63	415	125	115	70	45	50	80	57.5	50	
125	80/90	445	130	140/145	77	50	60	87	70	60	
140	90/100	480	141	160/165	85	60	65	93	75	70	
160	100/110	520	153	185/190	98	65	70	108	85	80	
180	110/125	560	168	205/210	105	70	80	115	95	90	
200	125/140	600	182	230/244	118	80	90	128	110	100	
220/225	125/140/160	610	171	250/267	135	95	100	142	120	110	without lock nut
250	140/160/180	650	172	292/298	135	95	100	140	130	125	
280	160/180/200	740	202	324/343	170	110	125	170	155	140	
300	180/200/220	800	228	356/368	180	130	140	185	170	150	
320	180/200/220	880	243	368/381	200	140	150	200	175	160	
360	200/220/250	980	257	419/432	220	150	160	220	180	180	
400	220/250	1120	290	470	240	160	170	250	220	200	

**HYDRA Tech**

NAME  
CYLINDER D/d x S  
CM250 CHCH

DRAWING NO  
CM250-CHCH-A

INDEX